
# Docking Drawer®

Safety Interlock Disconnect Kit with Corner Mount Limit Switch Tear Sheet

#### 0290-6120W66

Revision 1





Docking Drawer's Safety Interlock Disconnect Kit with Corner Mount Limit Switch enhances the safety of stationary kitchen appliance garages by de-energizing the power outlet and up to 4 connected devices whenever the cabinet door is closed. This safety outlet can be wired in-series with the included receptacles, featuring (4) 20amp AC ports. ETL Listed to UL 498 and CSA 22.2 #42 and approved for use in the US & Canada\*. Possible applications include:

- Appliance Garages with toasters, microwaves, coffee makers, mixers, blenders, air fryers, and more.
- Any other application where devices are left plugged in and unattended behind a cabinet door.

\*The Authorities Having Jurisdiction (AHJ) has the final say on whether an installation meets the requirements of the Canadian Electrical Code.

### Docking 0290-6120W66 Drawer<sup>®</sup> Safety Interlock Disconnect Kit with Corner Mount Limit Switch

Disconnect Specs		Limit Switch Specs	
	Interlock Switch Connector LED Indicator		Safety Interlock Connector Connects to the Safety Interlock Disconnect. Low Voltage Cable 6ft long Corner Mount
	— Mounting Bracket		Limit Switch Can install into the corner of any cabinet. Plunger detects the position of cabinet door and de- energizes when the door closes.
Input	100 - 125 VAC, 50/60 Hz	Type of Limit Switch	General Purpose Limit Switch
AC Output	20A@125VAC, 2500 VA MAX, 2 HP	Limit Switch Cable	6 ft low voltage cable
DC Output	24VDC @ 100mA MAX	Switch Length	1" (25.4mm)
		Switch Width	1" (25.4mm)
DC Power Supply	IEC Class II	Switch Height	1" (25.4mm)
Number of Receptacles	0		Can install in any cabinet or
Tamper Resistant	NA	Mounting Details	enclosed space behind the hinged side of the door
LED Indicator	Yes		
Conformance 🔬	UL60730, UL498, EN61558, EN60730, EN62386, CSA C22.2#42	Conformance Intertek	UL60730, UL498, EN61558, EN60730, EN62386, CSA C22.2#42
Intertek Environmental	-10 °C to +50 °C, non condensing	Warranty	2 Years
Warranty	2 Years		

#### **AC Outlet Specs**

AC Output	20A@120VAC
Number of Receptacles	(4) NEMA 5-20R
GFCI	No



## Resources & Downloads

Docking Drawer provides all of the necessary resources to plan a Safety Interlock Disconnect installation. Download the Spec Book and Installation Manuals at <u>dockingdrawer.com/downloads</u>

Project

Name:

#### **Ready to Order?**

Source directly from Docking Drawer or from one of our distribution partners. Learn more.

Lead Time - 2 weeks	Freight - FOB San Ramon	Warranty - 2 Years	Terms & Conditions

Source:

Where to Docking Drawer

Distributor