
# Docking Drawer®

Safety Interlock Disconnect with Corner Mount Limit Switch Tear Sheet

### 6120-2001x

Revision 1





Docking Drawer's Safety Interlock Disconnect with Corner Mount Limit Switch is designed to be used in both 15 and 20 amp applications. The Safety Interlock Disconnect with Corner Mount Limit Switch can be wired in series with up to 2 receptacles\* and can de-energize up to four devices or appliances at one time, when the cabinet door is closed. ETL Listed to UL 498 and CSA 22.2 #42 and approved for use in the US & Canada\*\*. Possible applications include:

- Appliance Garages with toasters, microwaves, coffee makers, coffee grinders, mixers, blenders, air fryers, etc.
- Or any enclosed space where devices are plugged in and left unattended

\*Receptacles not supplied by Docking Drawer

\*The Authorities Having Jurisdiction (AHJ) has the final say on whether an installation meets the requirements of the Canadian Electrical Code.

## Docking 6120-2001x Drawer<sup>®</sup> Safety Interlock Disconnect with Corner Mount Limit Switch

Disconnect Specs		Limit Switch Spece	5
	Interlock Switch Connector LED Indicator		<ul> <li>Safety Interlock</li> <li>Connector</li> <li>Connects to the Safety Interlock</li> <li>Disconnect.</li> <li>Low Voltage Cable</li> <li>6ft long</li> <li>Corner Mount</li> <li>Limit Switch</li> </ul>
	— Mounting Bracket		Can install into the corner of any cabinet. Plunger detects the position of cabinet door and de- energizes when the door closes.
Input	100 - 125 VAC, 50/60 Hz	Type of Limit Switch	General Purpose Limit Switch
AC Output	20A@125VAC, 2500 VA MAX, 2 HP	Limit Switch Cable	6 ft low voltage cable
DC Output	24VDC @ 100mA MAX	Switch Length	1" (25.4mm)
DC Power Supply	IEC Class II	Switch Width	1" (25.4mm)
Number of Receptacles	0	Switch Height	1" (25.4mm)
Tamper Resistant	 NA	Mounting Details	Can install in any cabinet or enclosed space behind the
LED Indicator	Yes		
	UL60730, UL498,		hinged side of the door
Conformance Intertek	EN61558, EN60730, EN62386, CSA C22.2#42	Conformance 💭	UL60730, UL498, EN61558, EN60730,
Environmental	-10 °C to +50 °C, non condensing	Warranty	EN62386, CSA C22.2#42 2 Years
Warranty	2 Years		

## Ready to Order?

**Resources &** 

**Downloads** 

Source directly from Docking Drawer or from one of our distribution partners. Learn more.

installation. Download the Spec Book and Installation Manuals at <u>dockingdrawer.com/downloads</u>

Docking Drawer provides all of the necessary resources to plan a Safety Interlock Disconnect

#### Project Name:

Where toDocking DrawerSource:Distributor